

500VA TRANSFORMER

Step-Up or Step-Down TransformersT

Application shot

are these the same as the 250?

This line of Espey products has dual primaries and secondaries. All four windings are identically rated so to permit series or parallel connections on either primary or secondary This unit also allows the user to make auto-transformer connections by connecting a primary group in series with a secondary group.

Features:

- Power -500VA
- Frequency - 50/60Hz
- Dielectric Strength - 250Vrms
- Terminals - Plated brass screw terminals
- Insulation class is 130°C standard, higher insulation classes are available.
- Primaries: Dual/tapped:
 - Parallel connected (104V, 110V, 120V)
 - Series connected (208V, 220V, 230V, 240V)
- Secondaries: Dual/tapped
 - Parallel connected (104V, 110V, 120V)
 - Series connected (208V, 220V, 230V, 240V)

Filter Inductor

Specifications:

ELECTRICAL SPECIFICATIONS

RATING	500VA, 50/60Hz, Single Phase
VOLTAGE	440VAC, 50/60 Hz, to 220 VAC
DIELECTRIC STRENGTH	2500 VAC, 60 Hz,winding to core and case for 1 minute
DUTY	Continuous
	Dual Primaries and Secondaries
	All windings are identically rated at 0V, 104V, 110V, 120V

MECHANICAL SPECIFICATIONS

need new diagrams